Fiber Optic Coupler Technical Specifications



Overview

Our Multimode Fiber Optic Couplers come standard with 62. 5/125 µm fiber, with low insertion loss and a broad operating wavelength range from 800 to 1600 nm. The 1x2 and 2x2 couplers are offered in both 50/50 (3 dB) and 10/90 coupling ratios. 1x4 and 1x8 port configurations are. Imagine you want to split one light signal into two paths. Fiber optic couplers are optical devices that connect three or more fiber ends, dividing one input between two or more outputs, or combining two or more inputs into one output. Our wideband couplers feature a broad spectral range with minimal spectral dependency, making these couplers ideal for. The FC Series PM fiber optic coupler uses fused biconical taper technology in a compact package, offering good uniformity, low excess loss, and very low polarization sensitivity for splitting or combining light over a wide wavelength range. Equipped with large ellipsoidal mirrors, the FiberMate2™ efficiently transmits the UV-Vis or FTIR beam of the spectrometer through.

© 2026 PROMETHEAS OPTICAL - All rights reserved

Article Content

Fiber optic coupler types, specs, and applications

Fiber optic coupler types, specs, and applications explained, including port configurations, insertion loss, and how to select the right coupler for your

Fiber Optic Couplers Specifications

Find Fiber Optic Couplers on GlobalSpec by specifications. Fiber optic couplers are optical devices that connect three or more fiber ends, dividing one input between two or more outputs, or combining two

OCT Fused Fiber Optic Couplers

Thorlabs offers a full selection of fiber optic couplers for other center wavelengths or with FC/PC connectors; please see our Fiber Optic Couplers guide for details.

1x2, 2x2 PM Fiber Optic Coupler

The FC Series PM fiber optic coupler uses fused biconical taper technology in a compact package, offering good uniformity, low excess loss, and very low polarization sensitivity for splitting or

FiberMate2™ Fiber Optic Coupler

The FiberMate2™ utilizes all reflective optics, optimizing the wavelength range of the fiber optic probe employed. FiberMate2™ comes with two SMA connectors

Multimode Fiber Optic Couplers | Fiber Optic Couplers

Our Multimode Fiber Optic Couplers come standard with 62.5/125 µm fiber, with low insertion loss and a broad operating wavelength range from 800 to 1600 nm. The

Single Mode Standard Coupler

Get product specifications, Download the Datasheet, Request a Quote and get pricing for Single Mode Standard Coupler on GoPhotonics.

1x2 / 2x2 Single Mode Ultra-Low PDL Broadband Fiber Optic

The FC Series fiber optic coupler is based on Agiltron''s fused biconical taper technology and compact packaging structure. It features good uniformity, low excess loss and very low polarization sensitivity.

OPTICO SM WBC 2x2 FBT Coupler Datasheet

OPTICO offers a wide range of narrowband and wideband 2x2 Single Mode Fiber Optic Couplers, also known as taps, as highlighted in the table to the right.

© 2026 PROMETHEAS OPTICAL - All rights reserved

OM1 vs OM2 vs OM3 vs OM4 vs OM5 Multimode Fiber

Compare OM1, OM2, OM3, OM4, and OM5 multimode fiber specs, distances, bandwidth, and applications. Essential guide for data center fiber

Harsh Environment Connector Solutions | ITT Cannon

ITT Cannon is a leading global manufacturer of connector products serving customers in aerospace, defense, medical, industrial and transportation markets

Single-mode optical fiber

In fiber-optic communication, a single-mode optical fiber, also known as fundamental- or mono-mode, is an optical fiber designed to carry only a single

Optical Fiber | Optical Fiber Products | Corning

Optical fiber broadband brings together a culture of innovation, quality, and manufacturing excellence to create life-changing products.

Fiber Optic Couplers Information

Fiber optic couplers are optical devices that connect three or more fiber ends, dividing one input between two or more outputs, or combining two or more inputs

S2-LCA-F-LCA-F_TechSpecs_191101

Fiber optic couplers provide feed-through patching via any industry-standard patch panel accommodating 13mm panel mount couplers. They connect two single mode fiber optic cables while

Handbook Optical fibres, cables and systems

The simultaneous availability of compact sources and of low-loss optical fibres led to a worldwide effort for developing optical fibre communication systems. The real research phase of fibre-optic

Data Sheet:

Data Sheet: Fiber Optic Coupler- Splitter 1 x N, 2 x N THOR FOC Series of optical couplers are used to split 1310 & 1550 nm light sources with minimal loss. The couplers are 19 inch rack mountable and

Microphone

Fiber-optic microphones are robust, resistant to environmental changes in heat and moisture, and can be produced for any directionality or impedance matching.

Related Video Reference

© 2026 PROMETHEAS OPTICAL - All rights reserved

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://prometheas.fr
Technical inquiry: https://prometheas.fr/project-desk.html
North American project region: Ashburn, Loudoun County, Virginia, United States

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 PROMETHEAS OPTICAL - All rights reserved